

Application No.: 10/735,521  
Preliminary Amendment

PATENT  
Page 2 of 27

Amendment to the Claims:

Please cancel claims 1-50 without prejudice.

Please enter claims 1-111 as follows:

R1 26 51  
1. (new) An apparatus for distributing one or more channels included within each of a plurality of N signals to one or more output devices, the apparatus comprising:

a crosspoint switch having a plurality of N crosspoint switch inputs and a plurality of crosspoint switch outputs, each of the N crosspoint switch inputs coupled to receive one of the N signals, the crosspoint switch operable to switchably couple any of the N crosspoint switch inputs to any one or more of the crosspoint switch outputs, wherein one or more channels included within a first of the N signals overlaps in frequency with one or more channels included within a second of the N signals; and

a plurality of band translation devices, each having an input coupled to a respective one of the crosspoint switch outputs and an output configured to couple to one or more output devices, each of the one or more band translation devices operable to pass one or more of the channels as supplied thereto, or to frequency translate one or more of the channels as supplied to respective one or more channels.

52 51  
2. (new). The apparatus of claim 1, wherein the one or more channels included within one or more of the N signals comprises respective one or more frequency division multiplexed channels, each of the one or more frequency division multiplexed channels having a different carrier frequency.

53 51  
3. (new). The apparatus of claim 1, wherein the one or more channels included within one or more of the N signals comprises at least one multiplexed channel, the multiplexed channel operating at a predetermined carrier frequency and comprising the content of two or more channels.

BEST AVAILABLE COPY

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 3 of 27

<sup>53</sup>  
54. (new) The apparatus of claim 2, wherein the content of the two or more channels comprises digital content, and wherein the multiplexed channel comprises a multiplexed digital channel.

<sup>55</sup>  
55. (new) The apparatus of claim 1, wherein at least one of the N signals comprises a plurality of frequency bands.

<sup>56</sup>  
56. (new) The apparatus of claim 4, wherein the crosspoint switch and the plurality of band translation devices are included within an integrated circuit.

<sup>57</sup>  
57. (new) The apparatus of claim 4, wherein two or more band translation devices are coupled to the same local oscillator source.

<sup>58</sup>  
58. (new) The apparatus of claim 4, wherein two or more band translation devices are coupled to different variable local oscillator sources.

<sup>59</sup>  
59. (new) The apparatus of claim 4, wherein the output of each one of the band translation devices is configured to couple to a single output device.

<sup>60</sup>  
60. (new) The apparatus of claim 4, wherein the outputs of two or more of the band translation devices are coupled together.

<sup>61</sup>  
61. (new) The apparatus of claim 4, wherein the outputs of the two or more band translation devices are configured to couple to a single output device.

<sup>62</sup>  
62. (new) The apparatus of claim 4, wherein the output of at least one of the band translation devices is configured to couple to a plurality of output devices.

Application No.: 10/735,521  
Preliminary Amendment

PATENT  
Page 4 of 27

<sup>63</sup>  
13. (new) The apparatus of claim 10, further comprising a signal combiner having (i) a plurality of inputs coupled to respective plurality of band translation device outputs, and (ii) an output coupled to one or more output devices.

<sup>64</sup>  
14. (new) The apparatus of claim 13, wherein the output of the signal combiner is coupled to each of the one or more output devices.

<sup>65</sup>  
15. (new) The apparatus of claim 13, wherein the output of the signal combiner is coupled to a first subset of the one or more output devices; the apparatus further comprising a second signal combiner having a plurality of inputs coupled to respective plurality of band translation device outputs, and an output coupled to a second subset of one or more output devices.

<sup>66</sup>  
16. (new) The apparatus of claim 13, further comprising a respective plurality of filters, each respective filter coupled between a band translation device output and a signal combiner input.

<sup>67</sup>  
17. (new) The apparatus of claim 16, wherein the plurality of filters are selected from the group consisting of a high pass filter, a lowpass filter, a bandpass filter, and a diplexer.

<sup>68</sup>  
18. (new) The apparatus of claim 16, wherein the plurality of filters are implemented separately from the crosspoint switch.

<sup>69</sup>  
19. (new) The apparatus of claim 18, wherein the plurality of filters, the crosspoint switch and the plurality of band translation devices are monolithically formed on an integrated circuit.

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 5 of 27

<sup>70</sup>  
~~20~~ (new) The apparatus of claim <sup>51</sup>~~1~~, further comprising a plurality of variable gain amplifiers coupled to the crosspoint switch, each of the plurality of variable gain amplifiers operable to apply gain or attenuation to a signal input thereto.

<sup>71</sup>  
~~21~~ (new) The apparatus of claim <sup>70</sup>~~20~~, wherein each of the plurality of variable gain amplifiers comprises an input coupled to receive a respective one of the N signals, a control input, and an output coupled to one of the inputs of the crosspoint switch, wherein each of the variable gain amplifiers is operable, responsive to a control signal received at the control input, to apply gain or attenuation to a signal input thereto.

<sup>72</sup>  
~~22~~ (new) The apparatus of claim <sup>71</sup>~~21~~, further comprising a respective plurality of detectors, each detector having an input coupled to the input of one variable gain amplifier and an output coupled to the control port of said variable gain amplifier, each of the detectors operable to control the gain or attenuation level of the variable gain amplifier as a function of the power detected.

<sup>73</sup>  
~~23~~ (new) The apparatus of claim <sup>71</sup>~~21~~, further comprising a respective plurality of detectors, each detector having an input coupled to the output of one variable gain amplifier and an output coupled to the control port of said variable gain amplifier, each of the detectors operable to control the gain or attenuation level of the variable gain amplifier as a function of the power detected.

<sup>74</sup>  
~~24~~ (new) The apparatus of claim <sup>71</sup>~~21~~, wherein the crosspoint switch, the plurality of band translation devices, and the plurality of variable gain amplifiers are included within an integrated circuit.

<sup>75</sup>  
~~25~~ (new) The apparatus of claim <sup>51</sup>~~1~~, further comprising at least one LNB converter operable to provide the N signals.

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 6 of 27

<sup>76</sup>  
28: (new) The apparatus of claim <sup>51</sup>7, wherein said crosspoint switch comprises a first crosspoint switch, said plurality of band translation devices comprises a plurality of first band translation devices, and said output devices comprise first output devices, the apparatus further comprising:

a second crosspoint switch having a plurality of N crosspoint switch inputs and a plurality of crosspoint switch outputs, each of the N second crosspoint switch inputs coupled to either: (i) a respective one of the first crosspoint switch inputs, or (ii) a respective one of the first crosspoint switch outputs, each of the second crosspoint switch outputs configured to couple to one or more second output devices, the second crosspoint switch operable to switchably couple any of the plurality of N second crosspoint switch inputs to any one or more of the plurality of second crosspoint switch outputs; and

a plurality of second band translation devices, each having an input coupled to a respective one of the second crosspoint switch outputs and an output configured to couple to one or more second output devices, each of the one or more second band translation devices operable to pass one or more channels as supplied thereto, or to frequency translate one or more of the channels as supplied to respective one or more channels.

<sup>77</sup>  
27: (new) The apparatus of claim <sup>76</sup>28, wherein the second crosspoint switch and the plurality of second band translation devices are included within a second integrated circuit.

<sup>78</sup>  
25: (new) The apparatus of claim <sup>76</sup>28, wherein the output of each one of the second band translation devices is configured to couple to a single second output device.

<sup>79</sup>  
29: (new) The apparatus of claim <sup>76</sup>28, wherein the outputs of two or more of the second band translation devices are coupled together.

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 7 of 27

<sup>80</sup> 30. (new) <sup>76</sup> The apparatus of claim 28, wherein the outputs of the two or more second band translation devices are configured to couple to a single second output device.

<sup>81</sup> 31. (new) <sup>76</sup> The apparatus of claim 28, wherein the output of at least one of the second band translation devices is configured to couple to a plurality of second output devices.

<sup>82</sup> 32. (new) <sup>76</sup> The apparatus of claim 28, wherein the output of at least one of the first band translation devices is coupled to at least one output of the second band translation devices.

<sup>83</sup> 33. (new) <sup>79</sup> The apparatus of claim 28, further comprising a second signal combiner having (i) a plurality of inputs coupled to respective plurality of second band translation device outputs, and (ii) an output coupled to one or more second output devices.

<sup>84</sup> 34. (new) <sup>83</sup> The apparatus of claim 28, further comprising a respective plurality of second filters, each respective second filter coupled between a second band translation device output and a second signal combiner input.

<sup>85</sup> 35. (new) <sup>76</sup> The apparatus of claim 28, further comprising a plurality of second variable gain amplifiers coupled to the second crosspoint switch, each of the plurality of second variable gain amplifiers operable to apply gain or attenuation to a signal input thereto.

<sup>86</sup> 36. (new) <sup>85</sup> The apparatus of claim 35, wherein the second crosspoint switch, the plurality of second band translation devices, and the plurality of second variable gain amplifiers are included within a second integrated circuit.

<sup>87</sup> 37. (new) <sup>87</sup> An apparatus for distributing one or more channels included within a plurality of N signals to one or more output devices, the apparatus comprising:  
a crosspoint switch having a plurality of N crosspoint switch inputs and a plurality of crosspoint switch outputs, each of the N crosspoint switch inputs coupled to receive

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 8 of 27

one of the N signals, the crosspoint switch operable to switchably couple any of the plurality of N crosspoint switch inputs to any one or more of the plurality of crosspoint switch outputs, and

a plurality of band translation devices, each having an input coupled to a respective one of the crosspoint switch outputs and an output configured to couple to one or more output devices, each of the one or more band translation devices operable to pass one or more channels as supplied thereto, or to frequency translate one or more of the channels as supplied to respective one or more channels.

wherein the outputs of at least two of the plurality of band translation devices are coupled together.

88 87  
38. (new) The apparatus of claim 37, wherein the one or more channels included within one or more of the N signals comprises respective one or more frequency division multiplexed channels, each of the one or more frequency division multiplexed channels having a different carrier frequency.

89 87  
39. (new) The apparatus of claim 37, wherein the one or more channels included within one or more of the N signals comprises at least one multiplexed channel, the multiplexed channel operating at a predetermined carrier frequency and comprising the content of two or more channels.

90 89  
40. (new) The apparatus of claim 39, wherein the content of the two or more channels comprises digital content, and wherein the multiplexed channel comprises a multiplexed digital channel.

91 87  
41. (new) The apparatus of claim 37, wherein at least one of the N signals comprises a plurality of frequency bands.

92 87  
42. (new) The apparatus of claim 37, wherein the crosspoint switch and the plurality of band translation devices are included within an integrated circuit.

Application No.: 10/735,521  
Preliminary Amendment

**PATENT**  
Page 9 of 27

~~93~~ <sup>87</sup>  
93. (new) The apparatus of claim 37, wherein two or more band translation devices are coupled to the same local oscillator source.

~~94~~ <sup>87</sup>  
94. (new) The apparatus of claim 37, wherein two or more band translation devices are coupled to different variable local oscillator sources.

~~95~~ <sup>87</sup>  
95. (new) The apparatus of claim 37, wherein the output of each one of the band translation devices is configured to couple to a single output device.

~~96~~ <sup>87</sup>  
96. (new) The apparatus of claim 37, further comprising at least one low noise block converter operable to provide the N signals.

~~97~~ <sup>87</sup>  
97. (new) The apparatus of claim 37, wherein the coupled output of the two or more band translation devices is configured to couple to a single output device.

~~98~~ <sup>87</sup>  
98. (new) The apparatus of claim 37, wherein the output of at least one of the band translation devices is configured to couple to a plurality of output devices.

~~99~~ <sup>87</sup>  
99. (new) The apparatus of claim 37, further comprising a signal combiner having (i) a plurality of inputs coupled to respective plurality of band translation device outputs, and (ii) an output coupled to one or more output devices, said output comprising the coupled output of the two or more band translation devices.

~~100~~ <sup>99</sup>  
100. (new) The apparatus of claim 99, wherein the output of the signal combiner is coupled to each of the one or more output devices.

~~101~~ <sup>99</sup>  
101. (new) The apparatus of claim 99, wherein the output of the signal combiner is coupled to a first subset of the one or more output devices; the apparatus further comprising a second signal combiner having a plurality of inputs coupled to respective



Application No.: 10/735,521  
Preliminary Amendment

PATENT  
Page 10 of 27

plurality of band translation device outputs, and an output coupled to a second subset of one or more output devices.

102 99  
52. (new) The apparatus of claim 49, further comprising a respective plurality of filters, each respective filter coupled between a band translation device output and a signal combiner input.

103 87  
53. (new) The apparatus of claim 37, further comprising a plurality of variable gain amplifiers coupled to the crosspoint switch, each of the plurality of variable gain amplifiers operable to apply gain or attenuation to a signal input thereto.

104 103  
54. (new) The apparatus of claim 53, wherein each of the plurality of variable gain amplifiers comprises an input coupled to receive a respective one of the N signals, a control input, and an output coupled to one of the inputs of the crosspoint switch, wherein each of the variable gain amplifiers is operable, responsive to a control signal received at the control input, to apply gain or attenuation to a signal input thereto.

105 104  
55. (new) The apparatus of claim 54, further comprising a respective plurality of detectors, each detector having an input coupled to the input of one variable gain amplifier and an output coupled to the control port of said variable gain amplifier, each of the detectors operable to control the gain or attenuation level of the variable gain amplifier as a function of the power detected.

106 104  
56. (new) The apparatus of claim 54, further comprising a respective plurality of detectors, each detector having an input coupled to the output of one variable gain amplifier and an output coupled to the control port of said variable gain amplifier, each of the detectors operable to control the gain or attenuation level of the variable gain amplifier as a function of the power detected.

Application No.: 10/735,521  
Preliminary Amendment

PATENT  
Page 11 of 27

107  
57. (new) The apparatus of claim 54, wherein the crosspoint switch, the plurality of band translation devices, and the plurality of variable gain amplifiers are included within an integrated circuit.

108  
58. (new) The apparatus of claim 57, wherein said crosspoint switch comprises a first crosspoint switch, said plurality of band translation devices comprises a plurality of first band translation devices, and said output devices comprise first output devices, the apparatus further comprising:

a second crosspoint switch having a plurality of N crosspoint switch inputs and a plurality of crosspoint switch outputs, each of the N second crosspoint switch inputs coupled to either: (I) a respective one of the first crosspoint switch inputs, or (II) a respective one of the first crosspoint switch outputs, each of the second crosspoint switch outputs configured to couple to one or more second output devices, the second crosspoint switch operable to switchably couple any of the plurality of N second crosspoint switch inputs to any one or more of the plurality of second crosspoint switch outputs; and

a plurality of second band translation devices, each having an input coupled to a respective one of the second crosspoint switch outputs and an output configured to couple to one or more second output devices, each of the one or more second band translation devices operable to pass one or more channels as supplied thereto, or to frequency translate one or more of the channels as supplied to respective one or more channels,

wherein the outputs of at least two of the plurality of second band translation devices are coupled together.

109  
59. (new) The apparatus of claim 58, wherein the second crosspoint switch and the plurality of second band translation devices are included within a second integrated circuit.

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 12 of 27

- 110 108  
80. (new) The apparatus of claim 58, wherein the coupled output of the two or more second band translation devices is configured to couple to a single second output device.
- 111 108  
81. (new) The apparatus of claim 58, wherein the output of at least one of the second band translation devices is configured to couple to a plurality of second output devices.
- 112 108  
82. (new) The apparatus of claim 58, wherein the output of at least one of the first band translation devices is coupled to at least one output of the second band translation devices.
- 113 108  
83. (new) The apparatus of claim 58, further comprising a second signal combiner having (i) a plurality of inputs coupled to respective plurality of second band translation device outputs, and (ii) an output coupled to one or more second output devices; said output comprising the coupled output of the two or more band translation devices.
- 114 113  
84. (new) The apparatus of claim 83, further comprising a respective plurality of second filters, each respective second filter coupled between a second band translation device output and a second signal combiner input.
- 115 108  
85. (new) The apparatus of claim 58, further comprising a plurality of second variable gain amplifiers coupled to the second crosspoint switch, each of the plurality of second variable gain amplifiers operable to apply gain or attenuation to a signal input thereto.
- 116 115  
86. (new) The apparatus of claim 58, wherein the second crosspoint switch, the plurality of second band translation devices, and the plurality of second variable gain amplifiers are included within a second integrated circuit.
- 117  
87. (new) In a signal distribution system having a crosspoint switch having N inputs operable to receive a respective plurality of N signals and a plurality of crosspoint switch

Application No.: 10/735,521  
Preliminary Amendment

PATENT  
Page 13 of 27

outputs; a respective plurality of band translation devices coupled to the crosspoint switch outputs, and one or more output devices coupled to at least one of the plurality of band translation devices, a method for distributing one or more channels included within any one of the plurality of N received signals to the one or more output devices, the method comprising:

receiving a plurality of N signals into the crosspoint switch, the crosspoint switch input having a respective plurality of N inputs, wherein one or more channels included within a first of the N signals overlaps in frequency one or more channels included within a second of the N signals;

selectively switching the crosspoint switch, whereby any of the plurality of N received signals is coupled to any one or more of the crosspoint switch outputs;

supplying one or more crosspoint switch output signals to respective band translation devices, each of the one or more crosspoint switch output signals including one or more channels;

controlling one or more of the plurality of the band translation devices either to pass the one or more channels as supplied therethrough, or to frequency translate one or more of the channels as supplied to respective one or more channels; and

outputting the pass-thru or frequency-translated channels to one or more output devices operable to render the one or more channels supplied thereto.

118 117  
88. (new) The method of claim 87, wherein said crosspoint switch comprises the only crosspoint switch operable to distribute, to the one or more coupled output devices, one or more channels included within any of the plurality of N received signals.

119 117  
89. (new) The method of claim 87, wherein at least one of the N received signals comprises a plurality of frequency bands.

120 117  
90. (new) The method of claim 87, wherein:  
one or more channels are grouped into a frequency band; and

Application No.: 10/735,521  
Preliminary Amendment.

PATENT  
Page 14 of 27

controlling comprises frequency translating the one or more channels to the same frequency band.

121 117  
71. (new) The method of claim 67, wherein:

one or more channels are grouped into a frequency band; and  
controlling comprises frequency translating the one or more channels to a different frequency band.

122 117  
72. (new) The method of claim 67, wherein:

one or more channels are grouped into a frequency band; and  
controlling comprises passing through the one or more channels through the band translation device.

123 117  
73. (new) The method of claim 67, further comprising combining the one or more frequency-translated channels with one or more pass-through channels to provide a composite signal.

124 117  
74. (new) The method of claim 67, further comprising combining the one or more frequency-translated channels with one or more additional frequency-translated channels to provide a composite signal.

125 122  
75. (new) The method of claim 72, further comprising combining the one or more pass-through channels with an additional one or more pass-through channels to provide a composite signal.

126 117  
76. (new) The method of claim 67, wherein outputting the pass-thru or frequency-translated channels comprises outputting each of the pass-thru or frequency-translated channels onto a single line coupled to each of the one or more output devices.

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 16 of 27

127

117

77. (new) The method of claim 87, wherein outputting the pass-thru or frequency-translated channels comprises:

outputting one or more first pass-thru or frequency-translated channels onto a first line coupled to a first of the one or more output devices; and

outputting one or more second pass-thru or frequency-translated channels onto a second line coupled to a second of the one or more output devices.

128

117

78. (new) The method of claim 87, wherein controlling comprises:

upconverting at least one of the channels from the first frequency to an intermediate frequency; and

downconverting the at least one of the channels from the intermediate frequency to the second frequency.

129

117

79. (new) The method of claim 87, wherein controlling comprises:

downconverting at least one of the channels from the first frequency to an intermediate frequency; and

upconverting the at least one of the channels from the intermediate frequency to the second frequency.

130

129

80. (new) The method of claim 78, wherein downconverting comprises downconverting the at least one channel to baseband.

131

117

81. (new) The method of claim 87, further comprising filtering the pass-through or frequency-translated band of channels.

132

117

82. (new) The method of claim 87, wherein frequency translating comprises either (i) downconverting one or more of the channels from a first frequency to the second frequency, or (ii) up converting one or more of the channels from a first frequency to a second frequency.

Application No.: 10/738,521  
Preliminary Amendment

PATENT  
Page 16 of 27

133 117  
83. (new) The method of claim 87, further comprising variably adjusting a power level of either: (i) one or more of the N signals before input to respective N crosspoint switch inputs, (ii) at least one received signal output from the crosspoint switch, or (iii) one or more of the N signals prior to input to respective N crosspoint switch inputs and at least one received signal output from the crosspoint switch.

134 133  
84. (new) The method of claim 83, wherein variably adjusting a power level comprises attenuating the signals in (i), (ii), or (iii).

135 133  
85. (new) The method of claim 83, wherein variably adjusting a power level comprises amplifying the signals in (i), (ii), or (iii).

136 117  
86. (new) The method of claim 87, further comprising:  
receiving the plurality of the N signals into a second crosspoint switch, the second crosspoint switch input having a respective plurality of N inputs, wherein one or more channels included within a first of the N signals overlaps in frequency one or more channels included within a second of the N signals;  
selectively switching the second crosspoint switch, whereby any one of the plurality of N received signals is coupled to any one or more of the second crosspoint switch outputs;  
supplying one or more second crosspoint switch output signals to respective second band translation devices, each of the one or more second crosspoint switch output signals including one or more channels;  
controlling one or more of the plurality of the second band translation devices either to pass one or more channels as supplied thereto, or to frequency translate one or more of the channels as supplied to respective one or more channels; and  
outputting the pass-thru or frequency-translated channels to one or more second output devices operable to render the one or more channels supplied thereto.

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 17 of 27

137  
87. (new) An apparatus for distributing one or more channels included within each of a plurality of N satellite IF signals to one or more output devices, the apparatus comprising:

a crosspoint switch having a plurality of N crosspoint switch inputs and a plurality of crosspoint switch outputs, each of the N crosspoint switch inputs coupled to receive one of the N satellite IF signals, the crosspoint switch operable to switchably couple any of the plurality of N crosspoint switch inputs to any one or more of the plurality of crosspoint switch outputs, wherein one or more channels included within a first of the N satellite IF signals overlaps in frequency one or more channels included within a second of the N satellite IF signals; and

a plurality of band translation devices, each having an input coupled to a respective one of the crosspoint switch outputs and an output configured to couple to one or more output devices; each of the one or more band translation devices operable to pass one or more channels as supplied thereto, or to frequency translate one or more of the channels as supplied to respective one or more channels;

wherein the outputs of at least two of the plurality of band translation devices are coupled together.

138  
88. (new) The apparatus of claim 87, wherein the one or more channels included within one or more of the N satellite IF signals comprises respective one or more frequency division multiplexed channels, each of the one or more frequency division multiplexed channels having a different carrier frequency.

139  
89. (new) The apparatus of claim 87, wherein the one or more channels included within one or more of the N satellite IF signals comprises at least one multiplexed channel; the multiplexed channel operating at a predetermined carrier frequency and comprising the content of two or more channels.



Application No.: 10/735,521  
Preliminary Amendment

PATENT  
Page 18 of 27

- 140 139  
90. (new) The apparatus of claim 89, wherein the content of the two or more channels comprises digital content, and wherein the multiplexed channel comprises a multiplexed digital channel.
- 141 137  
91. (new) The apparatus of claim 87, wherein at least one of the N satellite IF signals comprises a plurality of frequency bands.
- 142 137  
92. (new) The apparatus of claim 87, wherein the crosspoint switch and the plurality of band translation devices are included within an integrated circuit.
- 143 137  
93. (new) The apparatus of claim 87, wherein two or more band translation devices are coupled to the same local oscillator source.
- 144 137  
94. (new) The apparatus of claim 87, wherein two or more band translation devices are coupled to different variable local oscillator sources.
- 145 137  
95. (new) The apparatus of claim 87, wherein the output of each one of the band translation devices is configured to couple to a single output device.
- 150 137  
96. (new) The apparatus of claim 87, wherein the outputs of the two or more band translation devices are configured to couple to a single output device.
- 151 137  
97. (new) The apparatus of claim 87, wherein the output of at least one of the band translation devices is configured to couple to a plurality of output devices.
- 152 137  
98. (new) The apparatus of claim 87, further comprising a signal combiner having (i) a plurality of inputs coupled to respective plurality of band translation device outputs, and (ii) an output coupled to one or more output devices.

Application No.: 10/735,621  
Preliminary Amendment

PATENT  
Page 19 of 27

<sup>149</sup> 98. (new) <sup>148</sup> The apparatus of claim 98, wherein the output of the signal combiner is coupled to each of the one or more output devices.

<sup>150</sup> 100. (new) <sup>148</sup> The apparatus of claim 98, wherein the output of the signal combiner is coupled to a first subset of the one or more output devices, the apparatus further comprising a second signal combiner having a plurality of inputs coupled to respective plurality of band translation device outputs, and an output coupled to a second subset of one or more output devices.

<sup>151</sup> 101. (new) <sup>148</sup> The apparatus of claim 98, further comprising a respective plurality of filters, each respective filter coupled between a band translation device output and a signal combiner input.

<sup>152</sup> 102. (new) <sup>151</sup> The apparatus of claim 101, wherein the plurality of filters are selected from the group consisting of a high pass filter, a lowpass filter, a bandpass filter, and a diplexer.

<sup>153</sup> 103. (new) <sup>151</sup> The apparatus of claim 101, wherein the plurality of filters are implemented separately from the crosspoint switch.

<sup>154</sup> 104. (new) <sup>151</sup> The apparatus of claim 101, wherein the plurality of filters, the crosspoint switch and the plurality of band translation devices are monolithically formed on an integrated circuit.

<sup>155</sup> 105. (new) <sup>137</sup> The apparatus of claim 87, further comprising a plurality of variable gain amplifiers coupled to the crosspoint switch, each of the plurality of variable gain amplifiers operable to apply gain or attenuation to a signal input thereto.

<sup>156</sup> 106. (new) <sup>155</sup> The apparatus of claim 105, wherein each of the plurality of variable gain amplifiers comprises an input coupled to receive a respective one of the N satellite IF

Application No.: 10/735,521  
Preliminary Amendment

PATENT  
Page 20 of 27

signals, a control input, and an output coupled to one of the inputs of the crosspoint switch, wherein each of the variable gain amplifiers is operable, responsive to a control signal received at the control input, to apply gain or attenuation to a signal input thereto.

<sup>157</sup>  
~~107.~~ <sup>156</sup> (new) The apparatus of claim 106, further comprising a respective plurality of detectors, each detector having an input coupled to the input of one variable gain amplifier and an output coupled to the control port of said variable gain amplifier, each of the detectors operable to control the gain or attenuation level of the variable gain amplifier as a function of the power detected.

<sup>158</sup>  
~~108.~~ <sup>156</sup> (new) The apparatus of claim 106, further comprising a respective plurality of detectors, each detector having an input coupled to the output of one variable gain amplifier and an output coupled to the control port of said variable gain amplifier, each of the detectors operable to control the gain or attenuation level of the variable gain amplifier as a function of the power detected.

<sup>159</sup>  
~~109.~~ <sup>156</sup> (new) The apparatus of claim 106, wherein the crosspoint switch, the plurality of band translation devices, and the plurality of variable gain amplifiers are included within an integrated circuit.

<sup>160</sup>  
~~110.~~ <sup>157</sup> (new) The apparatus of claim 87, further comprising at least one LNB converter operable to provide a respective at least one of the N satellite IF signals.

<sup>161</sup>  
~~111.~~ (new) An apparatus for distributing one or more channels included within each of a plurality of N satellite signals to one or more output devices, the apparatus comprising:

a first LNB unit operable to receive a plurality of the N satellite signals, the first LNB unit comprising:

a first LNB converter coupled to receive a plurality of the N satellite signals and operable to produce a plurality of first satellite IF signals;

Application No.: 10/735,521  
Preliminary Amendment

**PATENT**  
Page 21 of 27

a first crosspoint switch having a plurality of first crosspoint switch inputs coupled to receive respective first satellite IF signals and a plurality of first crosspoint switch outputs, the first crosspoint switch operable to switchably couple any of the first crosspoint switch inputs to any one or more of the first crosspoint switch outputs; and  
respective plurality of first band translation devices, each first band translation device having an input coupled to a respective one of the first crosspoint switch outputs and an output configured to couple to one or more output devices, each of the first band translation devices operable to pass one or more channels as supplied thereto, or to frequency translate one or more of the channels as supplied to respective one or more channels, wherein the outputs of the first band translation devices are coupled together to provide a first LNB unit output;

a second LNB unit operable to receive a plurality of the N satellite signals; the second LNB unit comprising:

a second LNB converter coupled to receive a plurality of the N satellite signals and operable to produce a plurality of second satellite IF signals;

a second crosspoint switch having a plurality of second crosspoint switch inputs coupled to receive respective second satellite IF signals and a plurality of second crosspoint switch outputs, the second crosspoint switch operable to switchably couple any of the second crosspoint switch inputs to any one or more of the second crosspoint switch outputs; and

respective plurality of second band translation devices, each second band translation device having an input coupled to a respective one of the second crosspoint switch outputs and an output configured to couple to one or more output devices, each of the second band translation devices operable to pass one or more channels as supplied thereto, or to frequency translate one or more of the channels as supplied to respective one or more channels, wherein the outputs of the second band translation devices are coupled together to provide a second LNB unit output; and

a signal combiner having inputs coupled to receive the first and second LNB unit outputs, and an output coupled to one or more output devices.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☒ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**